

INDOOR POWER ADAPTER 60W 96W 100W

Description:

Choose the perfect power solution with our Indoor Power Adapter series, available in 60, 96 and 100 watt options. These AC/DC adapters feature a plug-in design, a 3.5mm DC plug, and it is equipped with either a 2-pronged or 3-pronged wall plug for versatile and efficient indoor power supply.



Features:

- Universal AC input: 100~240Vac
- Protections: Short circuit / Overload
- No load power consumption < 0.5W /Over voltage
- Class II power (Isolated driver, so ground is not required)
- 2 pronged wall plug for the 60W
- 3 pronged wall plug for the 96W and 100W options
- 3.5MM DC plug



Applications:

- Indoor LED Driver
- LED Neon, LED urban decoration
- LED lighting advertising, LED display
- Safety protection apparatus
- Telecommunications, networks
- Vehicle lights, controller panels

Dimensions:

60W ⚡



96/100W ⚡



Connector:

DC Plug size: 3.5MM



Two pronged plug
for the 60 watt

Three pronged plug
for the 96 and 100 watt

Technical Specifications:

Input Current	1.48A max
Rated Input Voltage	100-240VAC
Output Voltage	24V
Efficiency	>87%
Startup time	2 sec
Operating temperature	32°F ~ 104°F
Storage temperature	-4°F ~ 140°F
Humidity	≤95%
Altitude	0-3000m

12V DC Out	60W	100W
AMPs	@5.0A MAX	@8.33A MAX
Hertz	50/60Hz	50/60Hz
AC In	100~240VAC	100~240VAC

24V DC Out	60W	96W
AMPs	@2.5A MAX	@4.0A MAX
Hertz	50/60Hz	50/60Hz
AC In	100~240VAC	100~240VAC

Ordering Guide:

Example: PWR-PLG-12V-60W-ID-G2

Power Adapter	Voltages	Wattage	Indoor	Version
PWR-PLG			ID	G2
	12V 24V	60W 60 Watt 96W 96 Watt 100W 100 Watt		