

WALL SCONCE

TECHNICAL SPECIFICATIONS:

- Material: die-casting aluminum + glass
- Socket: E26
- Finish: White and Bronze
- Dimensions: $\Phi 4 \frac{1}{4}'' * H18''$
- Net Weight: 6.61387 lbs
- IP Protection degrees: IP54



BULBS THAT CAN BE USED WITH THIS FIXTURE:

BR20



SKU: G-L2-BR20D-7W
 Wattage: 7W
 Input Voltage: 110-130V AC
 CCT: 2700K/5000K
 Beam Angle: 120°

BR30



SKU: G-L4-BR30D-11W
 Wattage: 11W
 Input Voltage: 110V AC
 CCT: 2700K, 3000K,
 4000K, 5000K
 Beam Angle: 120°

BR40



SKU: G-L4-BR40D-17W
 Wattage: 17W
 Input Voltage: 110V AC
 CCT: 2700K, 3000K,
 4000K, 5000K
 Beam Angle: 120°

BULBS THAT CAN BE USED WITH THIS FIXTURE:

PAR20



SKU: G-L4-PAR20D-7W
Wattage: 7W
Input Voltage: 120V AC
CCT: 2700K, 4000K, 5000K
Beam Angle: 40°

PAR30



SKU: G-L6-PAR30DSN
Wattage: 12W
Input Voltage: 110V AC
CCT: 2700K, 5000K
Beam Angle: 25°

PAR38-15W



SKU: G-L4-PAR38D
Wattage: 15W
Input Voltage: 120V AC
CCT: 2700K, 3000K,
4000K, 5000K
Beam Angle: 40°

PAR38-10W



SKU: MILI-PAR38-10W-RGBCB
Wattage: 10W
Input Voltage: 100-240Vac
CCT: 2700K~6500K
Beam Angle: 36°